



Typical Inspection Data:

| | |
|-----------------------|-------------------------|
| Density @ 20°C | 0.840 g/cm ³ |
| Viscosity @ 100°C | 13.3 cSt |
| Viscosity @ 40°C | 76 cSt |
| Viscosity Index | 179 |
| Viscosity CCS @ -35°C | 6000 cP |
| T.B.N. | 10.1 mg KOH/g |
| Sulphated Ash Mass | 1.1% |
| Zinc | 0.12% |
| Calcium | 0.26% |
| Phosphorus | 0.10% |
| Colour | Brown |
| Flash Point | 230°C |
| Pour Point | -45°C |

Eco MB 0W-40

Fully Synthetic

Official Approvals:

Approved under VW standard 502 00 and VW standard 505 00

Recommended by Comma for applications requiring:

ACEA A3/B4, API SN; MB 226.5;
Ford WSS-M2C937-A; RN 0700/0710

Product Features:

- Fully synthetic, high performance 0W-40 engine oil, for petrol and diesel vehicles including those with fuel injected and multivalved engines.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 05.04.2022