



Typical Inspection Data:

Density @ 20°C	1.048 g/cm ³
Viscosity @ -40°C	1300 cSt
Viscosity @ 100°C	2.3 cSt
Colour	Colourless to amber
Equilibrium Reflux Boiling Point	265°C
Wet Equilibrium Reflux Boiling Point	160°C
pH (50% EtOH)	9.1

DOT 4

Synthetic Brake Fluid

Recommended by Comma for applications requiring:

FMVSS 116 DOT 3, FMVSS 116 DOT 4, ISO 4925 (Classes 3 & 4), SAE J1703, SAE J1704

Product Features:

- The current standard brake fluid for most manufacturers.
- Ideal for cars with ABS systems.
- Can be mixed safely with DOT 3 and DOT 4 fluids.

Directions for use:

- **IMPORTANT** - Follow vehicle manufacturer's recommendations.
- Keep Brake Fluid clean and dry.
- Store in original container only.
- Keep container clean and tightly closed to prevent water absorption.
- Caution: Do not refill container and do not use for other liquids.
- Take care not to spill on paintwork. If spilt wash off with plenty of water. Do not rub.
- All brake fluids absorb moisture and therefore they must be checked or changed regularly.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 3 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 03-03-2021