



Typical Inspection Data:

Density @ 20°C	0.845 g/cm ³
Viscosity @ 100°C	10.8 cSt
Viscosity @ 40°C	61 cSt
Viscosity Index	170
Viscosity CCS @ -30°C	4200 cP
T.B.N.	7.4 mg KOH/g
Sulphated Ash Mass	0.7%
Zinc	0.08%
Calcium	0.13%
Phosphorus	0.07%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

Syner X 5W-30

Fully Synthetic

Recommended by Comma for applications requiring:

GM dexos1 Gen3, GM dexos1 Gen2 (backward compatible); API SP; ILSAC GF-6A; Chrysler MS 6395; GM 6094M and 4718M; Ford WSS-M2C946-A

Product Features:

- Fully synthetic, high performance 5W-30 oil for modern petrol engines.
- Provides low speed pre-ignition (LSPI) protection, particularly for small displacement turbo-charged engines. Aids fuel economy.
- Quick cold weather starting for ultra-fast protection.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 16-06-2023